

# tesa® 4983

30µm double sided transparent filmic tape

## PRODUCT INFORMATION

### Product Description

tesa® 4983 is a transparent, double-sided self-adhesive tape consisting of a PET backing and a tackified acrylic adhesive.

tesa® 4983 features especially:

- Thickness: 30µm
- Good adhesion level
- Excellent resistance to demanding environmental conditions
- Excellent handling performance in converting processes

### Main Application

- Lamination of cushioning materials to LCDs
- Fixing of reflection foil to LCD frame
- Splicing of thin plastic films
- Dielectric mounting of bus bar in thin film solar modules

### Technical Data

■ Backing material	PET film	■ Type of adhesive	tackified acrylic
■ Colour	transparent	■ Elongation at break	50 %
■ Total thickness	30 µm	■ Tensile strength	20 N/cm

### Adhesion to

■ Steel (initial)	5.2 N/cm	■ Steel (after 14 days)	7.6 N/cm
■ ABS (initial)	4.5 N/cm	■ ABS (after 14 days)	5.3 N/cm
■ Aluminium (initial)	4.1 N/cm	■ Aluminium (after 14 days)	5.5 N/cm
■ PC (initial)	5.2 N/cm	■ PC (after 14 days)	6.0 N/cm
■ PE (initial)	2.0 N/cm	■ PE (after 14 days)	3.3 N/cm
■ PET (initial)	4.2 N/cm	■ PET (after 14 days)	4.8 N/cm
■ PP (initial)	2.3 N/cm	■ PP (after 14 days)	3.7 N/cm
■ PS (initial)	4.0 N/cm	■ PS (after 14 days)	5.2 N/cm
■ PVC (initial)	3.6 N/cm	■ PVC (after 14 days)	6.4 N/cm

### Properties

■ Temperature resistance short term	200 °C	■ Resistance to chemicals	+
■ Temperature resistance long term	100 °C	■ Softener resistance	+
■ Tack	-	■ Static shear resistance at 23°C	+
■ Ageing resistance (UV)	++	■ Static shear resistance at 40°C	o
■ Humidity resistance	++		

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

#### tesa SE

Quickbornstraße 24  
20253 Hamburg  
Germany  
Phone: +49 (40) 4909 101

#### tesa tape inc.

5825 Carnegie Boulevard  
Charlotte, N.C. 28209  
United States of America  
Phone: +1 (704) 554 0707  
Fax: +1 (704) 553 5634  
<http://www.tesatape.com>

#### tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive  
#04-01 The Metropolis  
Tower 1  
Singapore 138588  
Tel: +65 6697 9888  
Fax: +65 6659 6390  
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.

#### Additional Info

Recognized according to UL 969, file number MH18055

Liner variants:

PV20 brown/blue logo glassine paper (71µm; 82g/m<sup>2</sup>)

For latest information on this product please visit <http://l.tesa.com/?ip=04983>

Page 2 of 2 / As of 07/04/14

#### tesa SE

Quickbornstraße 24  
20253 Hamburg  
Germany  
Phone: +49 (40) 4909 101

**tesa SE**  
A Beiersdorf Company

<http://www.tesa.com>

#### tesa tape inc.

5825 Carnegie Boulevard  
Charlotte, N.C. 28209  
United States of America  
Phone: +1 (704) 554 0707  
Fax: +1 (704) 553 5634  
<http://www.tesatape.com>

#### tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive  
#04-01 The Metropolis  
Tower 1  
Singapore 138588  
Tel: +65 6697 9888  
Fax: +65 6659 6390  
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.