

tesa® Wheel Rim Protection 50551

Transparent surface protection tape

PRODUCT INFORMATION

Product Description

tesa® 50551 transparent protection tape is the perfect solution for the protection of sensitive surfaces during transportation. The transparency of tesa® 50551 makes damages easily recognizable. Due to the good UV resistance tesa® 50551 can remain on the surface until the arrival at the end customer.

User benefits:

- Good adhesion to painted and chromed finishes
- Reliable bonding during vehicle transportation
- Offer cost savings due to reduction in rectification and final repair
- Excellent outdoor resistance for more than 8 months
- Effective prevention against brake disk corrosion - particularly after storage at maritime environments
- Reduction of damages caused by vehicle fixation during sea shipment
- Easy to apply. Ensuring simple, low cost application and removal processes
- No polishing after de-masking
- Easy disposal. Both, the film and the adhesive system are environmentally friendly

Main Application

Wheel Rim Protection during transportation in the automotive

Technical Data

■ Backing material	PE film	■ Elongation at break	300 %
■ Total thickness	70 µm	■ Tensile strength	17 N/cm
■ Type of adhesive	acrylic	■ UV-resistance	32 weeks
■ Adhesion to steel	1.2 N/cm		

Properties

■ Easy to remove	yes	■ Paint compatibility	+
■ Suitable for die cutting	yes	■ Resistance to chemicals	+

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=50551>

Page 1 of 1 / As of 07/04/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.