

tesa® 51134

Surface protection and masking tape

PRODUCT INFORMATION

Product Description

tesa® 51134 is a transparent self-adhesive polyethylene tape with an acrylic adhesive for masking large areas of plastic parts during professional painting processes. Furthermore tesa® 51134 is an interior protection tape for slightly structured surfaces.

Main Application

- Masking during painting applications
- Protection of various surfaces against dust and damage

Technical Data

■ Backing material	PE film	■ Elongation at break	200 %
■ Total thickness	84 µm	■ Tensile strength	15 N/cm
■ Type of adhesive	acrylic	■ Temperature resistance	90 °C
■ Adhesion to steel	2.4 N/cm		

Properties

■ Easy to remove	yes	■ Powerwash resistance	+
■ Paint anchorage	++	■ Flame retardant	+

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=51134>

Page 1 of 1 / As of 07/25/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.